

## TAPPCO lubricants

Sudan - Khartoum, P.O. Box: 13368

Khartoum (2) - Block No. 5 - Building No. 19

Tel: (+249) 183 5794 49 Fax: (+249) 183 5794 47

Email: Sales@Tappco-lubes.com Technical@Tappco-lubes.com

www.Tappco-lubes.com



Product Technical  
Specification

# ATF DEXRON III

*Semi synthetic automatic transmission fluid*

## Product Description:

This product is a multi-purpose automatic transmission fluid (ATF) for commercial and passenger car gearboxes meeting a very wide range of specifications.

The automatic transmission is one of the most complicated mechanisms in modern automotive engineering and consequently requires complex fluids for efficient operation.

This product is manufactured from premium synthetic base stocks and high quality solvent refined base oils with specially selected additives and friction modifiers to produce a lubricant with outstanding durability. It demonstrates excellent frictional stability and offers extended fluid life even when under the most severe conditions.

## Applications:

This product is recommended for automatic transmission and power steering requirements in cars, vans, trucks, agricultural, construction and industrial machines where Dexron III specification is quoted.

## Benefits:

- Long oil life
- Improves clutch durability
- Can be used as a power steering fluid
- Excellent protection against wear
- Low foaming tendencies
- Compatible with all elastomers and other sealing materials
- High thermal stability

## Availability:

This product is available in:  
205 liters, 1 liter.

## Product Specification:

<b>General Motors</b>	<b>DEXRON III (H)</b>
<b>Allison</b>	<b>C-4, TES-389</b>
<b>Ford</b>	<b>MERCON</b>
<b>Mercedes-Benz</b>	<b>236.10, 236.9, 236.8, 236.7, 236.6, 236.5, 236.1</b>
<b>Caterpillar</b>	<b>TO-2</b>
<b>MAN</b>	<b>339F, 339 V1 &amp; Z1339 V2 &amp; Z2</b>
<b>Voith</b>	<b>55.6335 (G607)</b>
<b>Volvo</b>	<b>97340 ,97341</b>
<b>ZF</b>	<b>TE-ML 02F, 03D, 04D, 09, 11A,11B, 14A, 14B, 16L, 17C</b>

## Typical Test Data:

<b>Appearance</b>	<b>Red</b>
<b>Specific Gravity @ 15.6°C</b>	<b>0.882</b>
<b>Kinematic viscosity @ 100 °C (cSt)</b>	<b>7.91</b>
<b>Flash Point COC (°C)</b>	<b>205</b>
<b>Pour Point (°C)</b>	<b>-53</b>

## Health & Safety: (Group 3)

Please refer to the relevant health and safety data sheet, a copy of which is freely available to all of our customers.

Issued by: TAPPCO - Technical Department - August 2016

Approved by: EXOL UK - Technical Department.