

## TAPPCO lubricants

Sudan - Khartoum, P.O. Box: 13368

Khartoum (2) - Block No. 5 - Building No. 19

Tel: (+249) 183 5794 49 Fax: (+249) 183 5794 47

Email: Sales@Tappco-lubes.com Technical@Tappco-lubes.com

www.Tappco-lubes.com



Product Technical  
Specification

# CYCLONE TURBINE OIL

## Product Description:

These oils are manufactured from the highest quality solvent refined mineral base oils fortified with a proprietary turbine oil additive.

The state of the art additive system offers outstanding protection against oxidation, gives long term corrosion protection, and helps retain good oil demulsibility in the presence of water.

## Applications:

These oils have a number of vital functions to perform. They must lubricate and cool the turbine and generator bearings, couplings and reduction gears as well as protect the system from rust, corrosion, and oxidation. The use of Cyclone Turbine oils ensures that all of these functions are met.

## Typical Test Data:

ISO VG	22	32	68	100	150
SG @ 15.6 °C	0.870	0.874	0.877	0.878	0.879
KV @ 40 °C (cSt)	22.0	32.0	68.0	100	150
Viscosity Index	98	98	98	99	99
Flash Point (°C)	215	220	225	227	228

## Availability:

This product is available in:  
205 liters.

## Performance Specifications:

These oils meet the following requirements:

Denison	HF-1
Cincinnati Milacron	P-38, P-45, P-54, P-55, P-57, & P-62
DIN	51524 Part 1
US Steel	126
Military	MIL-L-17672 C
AFNOR	E-48600 HL

## Benefits:

- Excellent oxidation stability.
- Superior demulsification in the presence of water.
- Long term corrosion protection.

## Health & Safety: (Group 4)

Please refer to the relevant health and safety data sheet, a copy of which is freely available to all of our customers.

Issued by: TAPPCO - Technical Department - August 2016

Approved by: EXOL UK - Technical Department.