

TAPPCO lubricants

Sudan - Khartoum, P.O. Box: 13368

Khartoum (2) - Block No. 5 - Building No. 19

Tel: (+249) 183 5794 49 Fax: (+249) 183 5794 47

Email: Sales@Tappco-lubes.com Technical@Tappco-lubes.com

www.Tappco-lubes.com



Product Technical
Specification

MARINE TWO STROKE TC-W3

Product Description:

This product is a premium quality, specially formulated, outboard two stroke oil.

This product is manufactured from a special blend of highly refined mineral oils balanced proportionately with synthetic based ashless additives to provide superior protection and extend engine life. It exceeds the requirements of the widely quoted national Marine Manufacturers Association NMMA.

Applications:

This product is suitable for the majority of water-cooled out board two strokes. It is suitable for high output engines ranging from 15 H.P up to and exceeding 70 H.P.

Always refer to the manufacturers handbook for mixing ratios.

Benefits:

- Provides extended engine life through superior protection.
- Non toxic to marine life.
- Reduces spark plug fouling.
- Extends valve life by reducing exhaust port deposits

Availability:

This product is available in:
200^{liters}, 30^{liters}.

Product Specification:

NMMA	TC-W3
API	TD

Typical Test Data:

Appearance	Amber
Specific Gravity @15.6 °C	0.868
Kinematic Viscosity @100 °C (mm ² /s)	4.05
Flash Point COC (°C)	140

Health & Safety: (Group 1A)

Please refer to the relevant health and safety data sheet, a copy of which is freely available to all of our customers.

Issued by: TAPPCO - Technical Department - August 2016

Approved by: EXOL^{UK} - Technical Department.