

## TAPPCO lubricants

Sudan - Khartoum, P.O. Box: 13368

Khartoum (2) - Block No. 5 - Building No. 19

Tel: (+249) 183 5794 49 Fax: (+249) 183 5794 47

Email: Sales@Tappco-lubes.com Technical@Tappco-lubes.com

www.Tappco-lubes.com



Product Technical  
Specification

# PPX MOTOR OIL SAE 50

## Product Description:

This product is top high performance motor oil designed to provide the motorists with a lubricant which will keep clearly ahead of the emerging generation of higher performance, more sophisticated engine designs, many of which are turbo charged.

## Applications:

This product can be used in a very wide range of highly advanced petrol, naturally aspirated and turbo-charged fitted to passenger cars, light commercial and heavy haulage vehicles making it ideal for mixed fleet operations.

## Benefits:

- Protection against sludging.
- Stay in grade performance.
- Excellent protection against wear and corrosion.

## Availability:

This product is available in:  
200 liters, 4 liters, 3 liters, 1 liter.

## Product Specification:

<b>API</b>	<b>SL</b>
<b>SAE</b>	<b>50</b>
<b>ACEA</b>	<b>A3,B3,B4</b>
<b>CCMC</b>	<b>G4/D4</b>
<b>Military Spec.</b>	<b>Mil-L- 46152 E</b>
<b>VW</b>	<b>505</b>
<b>M B</b>	<b>228.1</b>
<b>MAN</b>	<b>271</b>
<b>VOLVO</b>	<b>VDS</b>

## Typical Test Data:

<b>Specific Gravity @ 15.6°C</b>	<b>0.888</b>
<b>Kinematic viscosity @ 100 °C (cSt)</b>	<b>20.6</b>
<b>Kinematic viscosity @ 40 °C (cSt)</b>	<b>196.07</b>
<b>Viscosity Index (VI)</b>	<b>123</b>
<b>Flash Point COC (°C)</b>	<b>240</b>
<b>Pour Point (°C)</b>	<b>-29</b>
<b>TBN (mgKOH/g)</b>	<b>10</b>

## Health & Safety: (Group 1)

Please refer to the relevant health and safety data sheet, a copy of which is freely available to all of our customers.

Issued by: TAPPCO - Technical Department - August 2016

Approved by: EXOL UK - Technical Department.