

TAPPCO lubricants

Sudan - Khartoum, P.O. Box: 13368

Khartoum (2) - Block No. 5 - Building No. 19

Tel: (+249) 183 5794 49 Fax: (+249) 183 5794 47

Email: Sales@Tappco-lubes.com Technical@Tappco-lubes.com

www.Tappco-lubes.com



Product Technical
Specification

REFRIDGE OIL 68

Product Description:

These products are a range of premium quality, low pour point compressor oils.

Lubricants for compressors vary dependent upon the type of compressor e.g. reciprocating, rotary, screw and also the gas being compressed e.g. air, nitrogen and refrigerants etc. With these features firmly in mind the range of Refridge oils have been designed for a wide range of manufacturers specifications and requirements.

This product range of compressor oils are manufactured using carefully selected naphthenic base oils that possess inherently low temperature capabilities. They reduce the formation of ice crystals if water is present in the lubricant and remain fluid even at the lowest temperatures encountered in their operating cycle.

Applications:

These products are suitable for domestic and industrial refrigerant compressors.

Benefits:

- 🔥 Excellent low temperature performance.
- 🔥 Improved evaporator efficiency.

Availability:

This product is available in:
200^{liters}, 30^{liters}.

Product Specification:

	Freon (R22)
Types of refrigerant	Ammonia
	Carbon Dioxide

Typical Test Data:

Specific Gravity @ 15.6°C	0.895
Kinematic viscosity @ 40 °C (cSt)	66.51
Viscosity Index (VI)	74
Flash Point COC (°C)	223
Appearance	Amber

Health & Safety: (Group 12)

Please refer to the relevant health and safety data sheet, a copy of which is freely available to all of our customers.

Issued by: TAPPCO - Technical Department - August 2016

Approved by: EXOL^{UK} - Technical Department.