

TAPPCO lubricants

Sudan - Khartoum, P.O. Box: 13368

Khartoum (2) - Block No. 5 - Building No. 19

Tel: (+249) 183 5794 49 Fax: (+249) 183 5794 47

Email: Sales@Tappco-lubes.com Technical@Tappco-lubes.com

www.Tappco-lubes.com



Product Technical
Specification

TRANSMISSION T0-4

Product Description:

A range of heavy-duty power transmission, final drive fluids and hydraulic fluids.

The range of T0-4 products have been formulated using high quality base oils and specially approved metallic and non metallic friction modifying performance additives to meet the exacting requirements of the Caterpillar T0-4 specification. They offer outstanding oxidation stability and improve the frictional and gear wear levels when compared to previous standards.

Applications:

The T0-4 range is suitable for off highway transmissions, drive trains and hydraulic systems. They are recommended for Caterpillar, Case, Komatsu and other off road industrial equipment. They are not recommended as a crankcase lubricant. Please refer to the manufacturer for specific viscosity requirement.

Benefits:

- Meets the latest Caterpillar T0-4 Specification.
- Outstanding oxidation stability.
- Excellent high temperature stability.
- Improved frictional performance.

Availability:

This product is available in:
205^{liters}, 30^{liters}.

Product Specification:

Caterpillar	T0-4
Allison	C-4
Komatsu micro clutch	Meets requirements
ZF	TE-ML 01 , 03

Typical Test Data:

SAE	10W	30	50
SG @ 15.6 °C	0.878	0.888	0.893
KV @ 40 °C (cSt)	36.81	94.62	216.04
KV @ 100 °C (cSt)	5.81	11.01	19.08
VI	98	101	99
Flash Point COC (°C)	195	210	238
Pour Point (°C)	-28	-30	-29

Health & Safety: (Group 3)

Please refer to the relevant health and safety data sheet, a copy of which is freely available to all of our customers.

Issued by: TAPPCO - Technical Department - August 2016

Approved by: EXOL^{UK} - Technical Department.