

TAPPCO lubricants

Sudan - Khartoum, P.O. Box: 13368

Khartoum (2) - Block No. 5 - Building No. 19

Tel: (+249) 183 5794 49 Fax: (+249) 183 5794 47

Email: Sales@Tappco-lubes.com Technical@Tappco-lubes.com

www.Tappco-lubes.com



Product Technical
Specification

TWO STROKE OIL TC

Product Description:

This product is a specially formulated, ash less two-stroke oil.

This Two Stroke Oil has been specially formulated from the latest additive technology and mineral components to produce a low smoke, clean burning product.

Applications:

This product is suitable in Motorcycles of low to medium output but can be used in a variety of two stroke applications such as, Mopeds, Go Karts, Lawnmowers, and Snowmobiles of less than 60 H.P.

Always refer to the manufacturers handbook for mixing ratios.

Benefits:

- Low smoke.
- Protection against piston and cylinder scuffing.
- Prevents pre ignition and power loss by reduces unwanted combustion chamber deposits.
- Protects against pre-ignition.
- Reduced exhaust blockage contaminants.

Availability:

This product is available in:
200 liters.

Product Specification:

API	TC TSC-3
JASO	FB
GLOBAL	ISO-L-EGB

Typical Test Data:

Appearance	Red
Specific Gravity @15.6 °C	0.880
Kinematic Viscosity @100°C (mm²/s)	8.45
Flash Point COC (°C)	140

Health & Safety: (Group 1A)

Please refer to the relevant health and safety data sheet, a copy of which is freely available to all of our customers.

Issued by: TAPPCO - Technical Department - August 2016

Approved by: EXOL UK - Technical Department.